

Handle Driven Restrictor

OPERATION



➤ March 2026



By Hydro



SOLEAL NEXT 75 Window

Restricted Opening





Starting position

- The window is fully closed.
- The handle is pointing straight downward (closed position).
- The handle is limited to the 90deg position.





Open to restricted position

- While the handle is still locked, gently rotate the handle upward until it reaches the 90° position (horizontal).
- The handle will stop at 90°. Do not try to turn it further.
- Pull the window open. The window will open only to the restricted opening limit.





Lock the window in the restricted position

- While the sash is open in restricted mode, rotate the handle back down to the closed (vertical) position.
- The window is now locked in the restricted position.
- **Do not leave the window open during windy conditions, strong gusts may cause damage to the gearing.**



Prepare to close the window

- To close the window from restricted mode, rotate the handle upward again to the 90° (horizontal) position.
- The window cannot be closed while the handle is fully down.



Close the window fully

- Gently push the window closed.
- Once fully shut, rotate the handle downward to the closed position.
- The window is now closed and locked.

*Instructions only applicable when using a Tilt before Turn handle from the TECHNAL range

Handle Driven Restrictor

OPERATION



➤ March 2026



By Hydro



SOLEAL NEXT 75 Window

Full Opening





Starting position

- The window is fully closed.
- The handle is pointing straight downward (closed position).
- The handle is limited to the 90deg position.




Unlock the handle

- Insert and turn the key until the lock disengages (180deg).
- The handle can now rotate past 90° into the full-opening position.





Open the sash fully

- Rotate the handle all the way up to the 180° position (fully vertical upward).
- Pull the window open.
- The sash will now open freely without restriction.



Prepare to close the window

- Before closing the sash, check that the handle is still at 180° (fully upward).
- **Closing the window with the handle in the wrong position can cause mechanical damage.**



Close and secure the window

- Gently push the sash closed until it fully seats in the frame.
- Rotate the handle downward to the closed position.
- Insert the key and lock the handle to prevent full opening if required.

*Instructions only applicable when using a Tilt before Turn handle from the TECHNAL range